## **Surfaced - Rough Lumber**

## **Sheet Stock**

- **Surfaced Lumber** is available in 4/4 (15/16") and 6/4 (17/16") thicknesses.
- WalzCraft stocks various grades of lumber. Because this is lumber taken directly from packs, there will be defects, hit and miss planing, and areas of poor color. If defects, areas of poor color and size limitations are a problem, or any other options are required, we suggest our Glued Up Panel (GUPFS) option, in *Section M16*, or our Face Frame Stock (FS100) in *Section J1*.
  - Glued up panels are matched to the same specifications as a door and may be ordered to your exact size.
- Options such as Simulated Distressing, Center Panel Face Routing and Finishing are *not available*.
- When ordering surfaced lumber you may specify a desired length and width. We will check our inventory for availability to see if we can meet your requirements.
- Surfaced lumber is not straight line ripped on either edge, unless you request it.
- Use Part #1035 when ordering Surfaced Lumber.
- Contact our Customer Support Team to check availability and to request a price quote.



Use this formula to calculate your board footage: Board Footage = (Width x Length x Nominal Thickness, divided by 144.) 4/4 = 1" Nominal Thickness (Actual Thickness = 15/16")  $6/4 = 1\frac{1}{2}$ " Nominal Thickness (Actual Thickness = 17/16")

\* Surfaced Lumber is selected directly from the packs of lumber used in our normal production. Please be sure to consider waste factors when ordering surfaced lumber. Board footage is "3 - Dimensional".

